



## GTO-10 Silicone Integral Sleeve Wire



- Rated for 10,000 VAC, 150°C.
- Conductor is tinned, copper 18 AWG, stranded, electrolytic tough pitch (ETP).
- Conforms to UL Standard 814 for gas tube sign and ignition cable.
- Meets the integral sleeving requirement of UL Standard 814.
- High performance silicon insulation material proven tough, versatile, and superior resistance to fire and flame, ozone, UV and corona.
- Withstands temperatures from -75°F to +500°F.
- Unequaled electrical properties exhibiting far less dielectric fatigue, excellent flex life under extreme temperature conditions.
- Currently available in black and white.

### U.S. Head Office

1059 Colite Drive · West Columbia, S.C. 29170  
P.O. Box 4064  
West Columbia, S.C. 29171-4064  
Tel: (803) 794-8061 (800) 869-6366 · FAX: (803) 794-8528  
E-Mail: [transco@earthlink.net](mailto:transco@earthlink.net)  
<http://www.transco-neon.com>

### U.K. Representative Office

6 Kemp Close, Chatham, Kent, ME5 9SP UK  
Tel: +44-7704559563  
E-mail: [tony.ralph@transco-intl.com](mailto:tony.ralph@transco-intl.com)  
[tonyralphcs@yahoo.com](mailto:tonyralphcs@yahoo.com)  
<http://www.transco-intl.com>

### China Representative Office

17G Huaguang Building, 333 Zhongshan Road,  
Wuxi Jiangsu, China 214001  
Tel: +86-510-82796979  
Fax: +86-510-82796689  
E-mail: [info@transco-intl.com](mailto:info@transco-intl.com)  
<http://www.transco-intl.com>